

POLYCAB IDEAS. CONNECTED.	POLYCAB INDIA LIMITED
PCC LP No. 03/2025-26 Dtd : 18th December 2025	
List of Products Covered in Our PCC LP	
Aluminium Armoured / Unarmoured Cables	
Copper Armoured / Unarmoured Cables	
HT Cables	
1.9 KV / 3.3 KV Cables for Solar	
Instrumentation Cables	
Rubber Cables	
JFTC Unarmoured/Armoured Cables & Telephone Dry Armoured Cables	
RS 485 Cables	
Fire Survival Cables	
FS Aluminium Cables	

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables , Armour (Aluminium wire for single core up to 70 sqmm balance Aluminium strip, Galvanised wire for cables upto 2x10 sqmm, 3x10 sqmm,4x6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Armoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XWaY / A2XFaY	A2XWY / A2XFY	A2XWY / A2XFY	A2XFY	A2XWY / A2XFY
2.5		213	238		265
4		242	260		303
6		294	321		384
10		372	415		527
16	239	423	446		564
25	315	452	594	690	738
35	382	564	755	838	956
50	470	730	982	1136	1277
70	601	978	1346	1531	1735
95	721	1207	1658	1920	2163
120	844	1455	2100	2428	2743
150	1006	1789	2578	2877	3373
185	1236	2150	3191	3642	4149
240	1527	2851	4075	4575	5357
300	1880	3494	5036	5628	6603
400	2374	4538	6437	7189	8243
500	2958	6127	8629	10162	11395
630	3649	7537	10969	12452	14958
800	4486				
1000	5517				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Round Wire Armouring		
- 2 x 16 & above	30%	
- 3 x 16 & 3.5CX25 & above	30%	
- 4 x 10 & above	30%	
- For Single core 95 & above	30%	
b) Stranding 10 sq.mm and below	10%	
c) Extruded PVC Innersheath Up 50	7.5%	
Extruded PVC Innersheath 70 & Above	4%	
d) HR PVC Insulation	17.5%	
e) HR PVC Inner Sheath	7.5%	
f) HR PVC Outer Sheath	7.5%	
g) Oxygen Index (FR)	4%	
h) PVC Insulated Cables	15%	

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Armoured		
		Power (Al.)		
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
		Power Single Core (Al.)		
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	11.5%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power Cables, Solid Aluminum conductor up to 10 sqmm balance stranded conductor, XLPE Insulated, cores laid up, PVC tape/Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 sheathed, 650/1100V grade as per IS 7098(Part 1) 1988

Aluminium Unarmoured

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	1 Core	2 Core	3 Core	3.5 Core	4 Core
	A2XY	A2XY	A2XY	A2XY	A2XY
4		136	170		204
6		190	225		274
10		274	307		360
16	133	279	345		458
25	192	360	506	642	675
35	249	472	670	726	805
50	318	593	825	983	1076
70	439	853	1189	1343	1545
95	565	1012	1446	1717	1842
120	711	1274	1962	2229	2372
150	879	1583	2309	2607	2936
185	1088	1888	2910	3336	3635
240	1381	2470	3756	4082	4749
300	1706	3019	4604	5291	5783
400	2197	3766	5745	6610	7392
500	2760	4805	8130	9121	10310
630	3420	6116	10200	12101	13797
800	4268				
1000	5381				

EXTRA FOR SPECIAL CONSTRUCTION:

a) Stranding 10 sq.mm and below	10%
b) Extruded PVC Innersheath Up 50	7.5%
Extruded PVC Innersheath 70 & Above	4%
c) HR PVC Insulation	17.5%
d) HR PVC Inner Sheath	7.5%
e) HR PVC Outer Sheath	7.5%
f) Oxygen Index (FR)	4%
g) PVC Insulated Cables	15%

Cable Size (Sq.mm)	FRLS Loading Factor		LSZH	
	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath
		Unarmd.		
Power (Al.)				
Upto 16	15%	11.5%	22.5%	30%
25 - 50	11.5%	11.5%	18%	22.5%
70 & above	7.5%	7.5%	22.5%	18%
Power Single Core (Al.)				
Upto 16	-N.A-	15%	-N.A-	37.5%
25 - 50	-N.A-	15%	-N.A-	30%
70 & above	-N.A-	12%	-N.A-	26%

● The above rates are exclusive of GST which shall be charged extra.

● This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Galvanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY	2XWY / 2XFY
4		557	746	956	1402	1766	1946
6		784	1077	1407	2039	2491	2858
10		1247	1752	2287	3101		
16	1041	1807	2505	3308	4348		

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XWY/2XFY			Number of Cores	2XWY/2XFY	
	1.5 Sq.mm.	2.5 Sq.mm.			1.5 Sq.mm.	2.5 Sq.mm.
2	284	401		14	1315	2067
3	361	518		16	1470	2348
4	446	668		19	1744	2764
5	542	820		24	2181	3461
6	645	965		27	2426	3881
7	710	1089		30	2706	4668
8	908	1329		37	3510	5453
10	1034	1530		44	4100	6368
12	1149	1778		61	6035	9232

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
1.5 sq.mm - 12 core & above	18%
2.5 sq.mm - 9 core & above	18%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.5%
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

FRLS Loading Factor- Control Cable			LSZH			
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath		
		Armoured				
2 to 4 Core	7.5%	9%	22.5%	22.5%		
5 to 10 Core	7.5%	6%	22.5%	22.5%		
12 & Above	7.5%	6%	18%	18%		

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core		3 Core	4 Core	
	2XY	2XY		2XY	2XY	
4		475		676	836	
6		693		998	1229	
10		1202		1692	2016	
16	870	1656		2404	3086	

Control Cables (Rate in Rs. Per Mtr.)

Number of Cores	2XY		Number of Cores	2XY	
	1.5 Sq.mm.	2.5 Sq.mm.		1.5 Sq.mm.	2.5 Sq.mm.
2	222	335	14	1089	1968
3	313	468	16	1304	2255
4	401	631	19	1560	2667
5	489	790	24	1977	3367
6	588	937	27	2183	3740
7	666	1068	30	2591	4434
8	811	1211	37	3356	5317
10	968	1387	44	3925	6338
12	1034	1698	61	5743	8723

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES) :

A) Tinning	3%	
B) Stranding (Upto 6 SQ.MM)	4%	
C) Extruded Innersheath	4%	
D OXYGEN INDEX (FR)	4%	
E) HR PVC Insulation	17.5%	
HR PVC I/S & O/S	7.5% Each	
F) FRLS Loading-Power Cable (upto 6 Sq.mm.)	11.50%	
FRLS Loading-Power Cable (10 Sq.mm. & above)	6%	
G) PVC Insulated Cables	15%	

FRLS Loading Factor- Control Cable			LSZH		
Cores	Inner Sheath	Outer Sheath	Inner Sheath	Outer Sheath	
	Unarmd				
2 - 4	7.5%	9%	22.5%	22.5%	
5 - 10	7.5%	6%	22.5%	22.5%	
12 & Above	7.5%	6%	18%	18%	

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994,with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Power/Control Copper Cables, Solid Copper conductor upto 6sqmm balance Stranded, XLPE Insulated, cores laid up, PVC tape innersheathed for Multicore Cables, Unarmoured/Armour (Glavanised wire for cables up to 10 x 1.5 sqmm, 8 x 2.5 sqmm, 2 x 10 sqmm, 3 x 10 sqmm, 4 x 6 sqmm balance all galvanised steel strip), extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Armoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	5 Core
	2XWaY / 2XFaY	2XWY / 2XFY	2XWY / 2XFY	2XFY	2XWY / 2XFY	2XWY / 2XFY
25	1574	3037	4146	4969	5465	7929
35	2138	4161	5839	6669	7753	10735
50	2890	5435	7893	9290	10519	14700
70	4059	8074	11525	13341	15184	23125
95	5394		15980	18299	21093	
120	6788		19594	24066	26281	
150	8444		24919	29113	33383	
185	10382		31676	37061	42310	
240	13338		41146	47837	54581	
300	16630		51858	59973	69405	
400	21738		66607	75800	92786	
500	27481					
630	34624					
800	43940					
1000	54808					

POLYCAB Brand Power/Control Copper Cables, Solid/Stranded Copper conductor, XLPE Insulated, cores laid up, PVC tape/PVC Extruded Innersheathed for Multicore Cables, Unarmoured, extruded PVC Type ST2 Sheathed, 650/1100 V grade as per IS 7098 (Part 1) 1988

Copper Unarmoured

(Rate in Rs. Per Mtr.)

Cable Size in sq.mm	1 Core	2 Core	3 Core	3.5 Core	4 Core	
	2XY	2XY	2XY	2XY	2XY	
25	1429	2820	3920	4671	5134	
35	1977	3907	5463	6289	7356	
50	2706	5357	7426	8894	9833	
70	3853	7640	10938	12830	14529	
95	5254		15650	18214	20374	
120	6622		18321	23291	26085	
150	8275		24532	28336	32606	
185	10156		30276	35400	40369	
240	13120					
300	16366					
400	21504					
500	27172					
630	34158					
800	43473					
1000	54343					

EXTRA FOR SPECIAL CONSTRUCTION (CONTROL CABLES):

A) Tinning	3%
B) Stranding (Upto 6 SQ.MM)	4%
C) Extruded Innersheath	4%
D) Round Wire Armouring	
1C x 95 sq. mm & above	9%
10 sq.mm - 4 core & above	18%
16 sq.mm - 2 core & above	18%
16 sq.mm - 3 core & above	18%
E) OXYGEN INDEX (FR)	4%
F) HR PVC Insulatoin	17.5%
HR I/S & O/S	7.5% Each
G) FRLS Loading-Power Cable (10 Sq.mm. & above)	6%
H) PVC Insulated Cables	15%

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guide-lines and are as per market convention, It may vary within the prescribed limit of IS:8130-1994, with related classes and tables:

- The above rates are exclusive of GST which shall be charged extra.
- This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

"POLYCAB" Brand Stranded Compact Circular Aluminium Conductor, Conductor Screen With Extruded Semi Conducting Compound, XLPE Insulated, Insulation Screening with extruded Semi Conducting Compound in combination with Copper Tape, cores laid up, innersheath of PVC tape, galvanised flat steel strip armoured and overall PVC Sheathed Cable conforming to IS 7098 / (PART-II) 1985 with latest amendments.

3 Core HT Cables

	(Rate in Rs. Per Mtr.)					
Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)	6.6 KV (UE) / 11 KV (E)	11 KV (UE)	22 KV (E)	33 KV (E)	33 KV (UE)
35		1845				
50		2205				
70	2479	2686				
95	2799	3047	4119	4204	5569	
120	3388	3680	4629	4723	6278	
150	3978	4310	5308	5416	6749	7302
185	4562	4914	5991	6114	7534	8121
240	5562	5954	7074	7218	8898	9419
300	6649	7042	8293	8464	10045	11056
400	8432	8812	10060	10264	12176	12802

EXTRA FOR SPECIAL CONSTRUCTION:

1) Extruded PVC Inner Sheath	4.5%	
2) Pressure Extruded PVC Innersheath	19.5%	
3) Round Wire Armouring - Up to 11 KV (E)	30%	
11 KV (UE) & Above	33%	
4) FRLS PVC Inner Sheath	7.5%	
5) FRLS PVC Outer Sheath	7.5%	
6) FR Sheath with Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

1 Core HT Cables

1 Core HT Cables

(Rate in Rs. Per Mtr.)

Size in Sq.mm.	3.3 KV (UE) / 6.6 KV (E)		6.6 KV (UE) / 11 KV (E)		11 KV (UE)		22 KV (E)		33 KV (E)		33 KV (UE)	
	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured	Al. Flat Strip Armoured	Al. Round Armoured
240	2039	2138	2240	2352	2537	2670	2596	2733	3339	3519	3824	4029
300	2336	2465	2568	2712	2889	3043	2956	3114	3948	4159	4248	4476
400	2840	2992	3080	3244	3431	3608	3507	3688	4530	4758	4793	5042
500	3623	3817	3755	3948	4310	4533	4310	4533	5337	5620	5562	5861
630	4377	4611	4496	4731	5093	5353	5093	5353	6207	6530	6463	6797
800	5440	5721	5516	5964	6101	6422	6101	6422	7346	7728	7665	8059
1000	6436	6774	7067	7444	7561	7952	7561	7952	8987	9421	9660	10166

EXTRA FOR SPECIAL CONSTRUCTION:

1) FRLS PVC Inner Sheath	11.5%	
2) FRLS PVC Outer Sheath	7.5%	
3) Oxygen Index	4.5%	

• The above rates are exclusive of GST which shall be charged extra.

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB Brand Aluminium Conductor, XLPE Insulated, flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
1 Core x 240	1485
1 Core x 300	1790
1 Core x 400	2255
1 Core x 630	3508

POLYCAB Brand Sector Shaped Aluminium Conductor, XLPE Insulated, innersheath of PVC tape, Galvanised steel wire / flat strip armoured and overall PVC Sheathed Cable conforming to IS 7098(Part 1) 1988

Sq.mm.	1.9 KV / 3.3 KV
	Armoured
3 Core x 25	803
3 Core x 35	910
3 Core x 50	1158
3 Core x 70	1408
3 Core x 95	1654
3 Core x 120	2164
3 Core x 150	2674
3 Core x 185	3149
3 Core x 240	3977
3 Core x 300	4872
3 Core x 400	6083

• This cancels all our previous Price Lists. This Price List is subject to change without prior notice.

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	148	0.75	172	1	192	1.5	229	2.5	314
CORE	3	0.5	176	0.75	214	1	242	1.5	299	2.5	415
CORE	4	0.5	198	0.75	238	1	280	1.5	350	2.5	503
CORE	5	0.5	222	0.75	276	1	326	1.5	415	2.5	603
CORE	6	0.5	251	0.75	314	1	377	1.5	482	2.5	726
CORE	7	0.5	272	0.75	347	1	419	1.5	545	2.5	817
CORE	8	0.5	303	0.75	387	1	467	1.5	615	2.5	919
CORE	10	0.5	353	0.75	461	1	566	1.5	748	2.5	1138
CORE	12	0.5	396	0.75	524	1	641	1.5	860	2.5	1283
CORE	14	0.5	456	0.75	586	1	734	1.5	1011	2.5	1517
CORE	16	0.5	501	0.75	660	1	822	1.5	1119	2.5	1710
CORE	19	0.5	563	0.75	747	1	947	1.5	1280	2.5	2009
CORE	24	0.5	680	0.75	939	1	1150	1.5	1584	2.5	2522
PAIR	1	0.5	148	0.75	172	1	192	1.5	229	2.5	314
PAIR	2	0.5	216	0.75	259	1	299	1.5	372	2.5	532
PAIR	3	0.5	259	0.75	326	1	387	1.5	495	2.5	735
PAIR	4	0.5	310	0.75	395	1	477	1.5	622	2.5	933
PAIR	5	0.5	362	0.75	468	1	573	1.5	759	2.5	1155
PAIR	6	0.5	418	0.75	545	1	664	1.5	885	2.5	1347
PAIR	7	0.5	459	0.75	597	1	746	1.5	1023	2.5	1536
PAIR	8	0.5	513	0.75	683	1	842	1.5	1134	2.5	1740
PAIR	10	0.5	615	0.75	811	1	1016	1.5	1383	2.5	2122
PAIR	12	0.5	697	0.75	947	1	1196	1.5	1619	2.5	2529
PAIR	14	0.5	767	0.75	1063	1	1342	1.5	1871	2.5	2881
PAIR	16	0.5	875	0.75	1170	1	1516	1.5	2090	2.5	3271
PAIR	19	0.5	994	0.75	1384	1	1766	1.5	2443	2.5	3835
PAIR	24	0.5	1242	0.75	1739	1	2199	1.5	3070	2.5	4820
TRIAD	1	0.5	180	0.75	216	1	244	1.5	302	2.5	418
TRIAD	2	0.5	299	0.75	371	1	411	1.5	530	2.5	767
TRIAD	3	0.5	371	0.75	466	1	532	1.5	698	2.5	1033
TRIAD	4	0.5	445	0.75	572	1	666	1.5	878	2.5	1303
TRIAD	5	0.5	515	0.75	685	1	797	1.5	1075	2.5	1600
TRIAD	6	0.5	594	0.75	792	1	935	1.5	1241	2.5	1880
TRIAD	7	0.5	657	0.75	878	1	1043	1.5	1399	2.5	2142
TRIAD	8	0.5	740	0.75	964	1	1168	1.5	1586	2.5	2443
TRIAD	10	0.5	877	0.75	1196	1	1420	1.5	1953	2.5	3012
TRIAD	12	0.5	998	0.75	1374	1	1663	1.5	2280	2.5	3565
TRIAD	14	0.5	1134	0.75	1570	1	1902	1.5	2621	2.5	4106
TRIAD	16	0.5	1257	0.75	1749	1	2138	1.5	2969	2.5	4655
TRIAD	19	0.5	1450	0.75	2034	1	2489	1.5	3468	2.5	5458
TRIAD	24	0.5	1796	0.75	2545	1	3110	1.5	4368	2.5	6867
QUAD	1	0.5	206	0.75	251	1	290	1.5	360	2.5	516

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	295	0.75	331	1	375	1.5	457	2.5	631
PAIR	3	0.5	378	0.75	422	1	497	1.5	610	2.5	859
PAIR	4	0.5	454	0.75	519	1	604	1.5	764	2.5	1059
PAIR	5	0.5	534	0.75	614	1	728	1.5	896	2.5	1293
PAIR	6	0.5	590	0.75	713	1	818	1.5	1050	2.5	1506
PAIR	7	0.5	674	0.75	789	1	940	1.5	1188	2.5	1713
PAIR	8	0.5	767	0.75	872	1	1052	1.5	1346	2.5	1953
PAIR	10	0.5	904	0.75	1064	1	1281	1.5	1645	2.5	2396
PAIR	12	0.5	1010	0.75	1238	1	1479	1.5	1940	2.5	2742
PAIR	14	0.5	1169	0.75	1392	1	1698	1.5	2192	2.5	3242
PAIR	16	0.5	1317	0.75	1566	1	1904	1.5	2473	2.5	3669
PAIR	19	0.5	1504	0.75	1802	1	2202	1.5	2888	2.5	4290
PAIR	24	0.5	1870	0.75	2264	1	2768	1.5	3642	2.5	5396
TRIAD	2	0.5	364	0.75	419	1	475	1.5	590	2.5	815
TRIAD	3	0.5	454	0.75	534	1	618	1.5	784	2.5	1111
TRIAD	4	0.5	553	0.75	664	1	769	1.5	964	2.5	1410
TRIAD	5	0.5	655	0.75	792	1	930	1.5	1187	2.5	1748
TRIAD	6	0.5	757	0.75	904	1	1067	1.5	1389	2.5	2053
TRIAD	7	0.5	837	0.75	1009	1	1197	1.5	1573	2.5	2333
TRIAD	8	0.5	936	0.75	1160	1	1361	1.5	1796	2.5	2662
TRIAD	10	0.5	1126	0.75	1403	1	1666	1.5	2203	2.5	3308
TRIAD	12	0.5	1303	0.75	1626	1	1946	1.5	2574	2.5	3877
TRIAD	14	0.5	1465	0.75	1850	1	2234	1.5	2970	2.5	4468
TRIAD	16	0.5	1649	0.75	2086	1	2508	1.5	3359	2.5	5069
TRIAD	19	0.5	1910	0.75	2424	1	2944	1.5	3950	2.5	5939
TRIAD	24	0.5	2396	0.75	3050	1	3711	1.5	4935	2.5	7518

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	1.5 Sq.mm.	2.5 Sq.mm.	4 Sq.mm.	6 Sq.mm.	10 Sq.mm.	16 Sq.mm.	25 Sq.mm.	35 Sq.mm.	50 Sq.mm.
1 Core						670	972	1348	1917
2 Core	177	272	381	572	968	1482	2236	3034	4319
3 Core	235	379	540	811	1378	2106	3144	4302	6128
4 Core	307	492	707	1074	1812	2757	4123	5659	8122
5 Core	372	642	949						
6 Core	447	700							
7 Core	488	787							
8 Core	566	960							
10 Core	748	1185							
12 Core	897	1398							
14 Core	1020	1616							
16 Core	1182	1839							
19 Core	1378	2150							
24 Core	1757	2737							

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED ELASTOMERIC SHEATHED CABLES (Rate Per Mtr)

Size	70 Sq.mm.	95 Sq.mm.	120 Sq.mm.	150 Sq.mm.	185 Sq.mm.	240 Sq.mm.	300 Sq.mm.	400 Sq.mm.	
1 Core	2694	3534	4481	5576	6796	8978	11244	14764	
3 Core	8634	11321	14351	17860	21766	28634	35913	46983	
4 Core	11319	14834	18927	23559	28729	37787	47340	62129	

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR				
0.5	132	207				

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED,G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	192	307	448	965	2049	3763

POLYCAB BRAND SOLID COPPER CONDUCTOR, POLYTHENE INSULATION, TWISTED PAIRS, LAY-UP, EXTRUDED ST1 GREY PVC INNER SHEATH, SINGLE LAYER GS ROUND WIRE ARMoured, EXT ST1 GREY PVC OUTER SHEATHED TELEPHONE ARMoured CABLE AS PER BSNL GR/WIR-06/03 MAR 2002

SIZE	5 PAIR	10 PAIR	20 PAIR			
0.5	154	292	464			

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	178
	22 AWG	0.32	195
	20 AWG	0.50	217
	18 AWG	0.80	256
	17 AWG	1.00	275
2 Pair	24 AWG	0.205	256
	22 AWG	0.32	287
	20 AWG	0.50	325
	18 AWG	0.80	398
	17 AWG	1.00	434

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	109
	22 AWG	0.32	123
	20 AWG	0.50	140
	18 AWG	0.80	174
	17 AWG	1.00	189
2 Pair	24 AWG	0.205	162
	22 AWG	0.32	195
	20 AWG	0.50	225
	18 AWG	0.80	290
	17 AWG	1.00	327

POLYCAB RS 485 CABLES (Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	195
	22 AWG	0.32	214
	20 AWG	0.50	239
	18 AWG	0.80	281
	17 AWG	1.00	303
2 Pair	24 AWG	0.205	281
	22 AWG	0.32	313
	20 AWG	0.50	356
	18 AWG	0.80	436
	17 AWG	1.00	479

POLYCAB RS 485 CABLES (Un Armoured)

500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Gauge	Size in Sq.mm.	Rate/Mtr.
1 Pair	24 AWG	0.205	119
	22 AWG	0.32	135
	20 AWG	0.50	154
	18 AWG	0.80	190
	17 AWG	1.00	211
2 Pair	24 AWG	0.205	181
	22 AWG	0.32	214
	20 AWG	0.50	248
	18 AWG	0.80	318
	17 AWG	1.00	358

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed Fire Survival Cables

				Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	395	490		598
2.5	490	628		774
4	576	756		946
6	748	1000		1264
10	1057	1445		1847
16	1401	1955		2572
25	1997	2877	3464	3780
35	2657	3853	4454	5086
50	3500	5117	6002	6777
70	4867	7149	8364	9469
95	6395	9417	10998	12482
120	7958	11767	14021	15624
150	9745	14430	16673	19147
185	12039	17844	20890	23673
240	15308	22735	26571	30191
300	18963	28170	32877	37445
400	24684	36722	42559	48814

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	439	540		654
2.5	540	679		832
4	629	809		1005
6	800	1058		1329
10	1118	1509		1919
16	1460	2018		2655
25	2073	2958	3555	3875
35	2738	3945	4554	5193
50	3591	5218	6112	6903
70	4977	7278	8504	9619
95	6524	9556	11153	12650
120	8094	11921	14206	15825
150	9906	14618	16883	19382
185	12220	18069	21140	23948
240	15524	23004	26871	30522
300	19220	28484	33227	37843
400	25007	37123	43010	49308

Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

				Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	457	565		684
2.5	560	706		866
4	648	835		1043
6	821	1091		1373
10	1143	1547		1970
16	1489	2064		2713
25	2119	3030	3641	3969
35	2792	4024	4648	5300
50	3660	5323	6238	7040
70	5068	7414	8667	9802
95	6621	9704	11336	12845
120	8213	12101	14431	16067
150	10060	14852	17160	19695
185	12422	18367	21488	24343
240	15763	23365	27295	31004
300	19502	28908	33730	38410
400	25359	37650	43642	50014

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/FRLS Inner Sheathed/GI Wire Strip Armoured/FRLS Sheathed FS Aluminium Power Cables

Sq.mm.	3 Core	4 Core
16	800	1034
25	1078	1371
35	1305	1684
50	1614	2091
70	2204	2870
95	2754	3586
120	3292	4313
150	3918	5131
185	4747	6200
240	5907	7726
300	7112	9332
400	8848	11591